



PORTABLE MAGNETIC DRILLS

		HMD130	HMD904	HMD905	HMD927	HMD2MT	HMD918	HMD917	HMD505 / HMD508	HMD934
		Low Profile	Fabricating				Heavy Duty Drilling			
Cutters	RotaLoc Plus™	✓	With Adapter	With Adapter	With Adapter	With Adapter	With Adapter	With Adapter	With Adapter	
	"12,000-Series"		✓	✓	✓	✓	✓	✓	✓	✓
	Copperhead™ Carbide Tipped		✓	✓	✓	✓	✓	✓	✓	✓
Model Specifications	Diameter Min./Max.	7/16" to 1-3/8" (12 - 35mm)	7/16" to 1-1/2" (12 - 38mm)	7/16" to 1-5/8" (12 - 41mm)	7/16" to 1-5/8" (12 - 41mm)	9/16" to 1-5/8" (14 - 41mm)	13/16" to 2" (21 - 50mm)	7/16" to 2-3/8" (12 - 60mm)	7/16" to 2-3/8" (12 - 60mm)	5/8" to 3-1/16" (16 - 77mm)
	Depth Max.	1" (25mm)	2" (50mm)	2" (50mm)	2" (50mm)	2" (50mm)	6" (152mm)	3" (76mm)	3" (76mm)	4" (100mm)
	Cutter Mounting	Bayonet Style	3/4" Double Flat	3/4" Double Flat	3/4" Double Flat	3/4" Double Flat	3/4" Double Flat	3/4" Double Flat	3/4" Double Flat	3/4" Double Flat
	No-Load R.P.M.	450	450	250 / 450	250 / 450	250 / 450	250 / 450	250 / 450	250 / 450 / 750	70 / 120 / 200 / 332
	Model Weight	23.8 lbs (10.8 kg)	28.9 lbs (13.1 kg)	35 lbs (15.9 kg)	43 lbs (19.5 kg)	40 lbs (18.1 kg)	44.2 lbs (20.1 kg)	46 lbs (20.9 kg)	45 lbs (20.4 kg)	72 lbs (32.6 kg)
	Thru-the-Tool Coolant		✓	✓	✓	✓	✓	✓	✓	✓
Available Accessories	Carrying Case Included	✓	✓	✓		✓	✓	✓	✓	
	Swivel Base		Optional	Optional	Optional			Optional		
	#2 Morse Taper					✓		With Adapter		
	Pipe Adapter		✓	✓	Manual Mode	✓	✓	✓	✓	Bracket Mount
	Tap Attachment		✓	✓	Manual Mode	✓	✓	✓		
	Vac-Pad™		✓	✓						
	Coolant Bottle		Optional	Included	Included	Included	Pressurized	Included	Included	Included
	Countersink Kit		✓	✓	Manual Mode	✓	✓	✓	✓	✓
	Twist Drill Adapter		✓	✓	Manual Mode	✓	✓	✓	✓	✓
	Ratchet Drive	✓	✓	✓		✓	✓	✓	✓	
	Arbor Extender		✓	✓	Manual Mode	✓	✓	✓	✓	✓
	Drill Chuck		✓	✓	Manual Mode	✓	✓	✓		
RotaLoc™ Spindle Adapter		✓	✓	Manual Mode	✓	✓	✓	✓		